

1ST

MATLAB - Lectures 1ST SEMESTER

LAB 1 IMPORTING AND EXPORTING DATA

Topics Covered:

1. The **load** command.
2. The **save** command.
3. The **xlsread** command.
4. The **xlwrite** command.

This is **useful** to know **how** to use **save** and **load** to transfer variables between the Workspace and a disk file.

1

1ST

IMPORTING AND EXPORTING DATA

IMPORTANCE DATA IN A MODEL

- What is a **model** ?
- The Atmospheric Science community includes a large and energetic group of researchers who devise and carry out measurements in the Atmosphere. This work involves instrument development, algorithm development, **data** collection, **data** reduction, and **data** analysis.
- **The data by themselves are just numbers.** In order to make physical sense of the **data**, some sort of **model** is needed. This might be a qualitative conceptual **model**, or it might be an analytical theory, or it might take the form of a **computer program**.

2

1ST

IMPORTING AND EXPORTING DATA

INPUT/OUTPUT (I/O) DATA

- ❑ **Importing data** is the process of retrieving(Input) data from sources external an ASCII text file.
- ❑ **Exporting data** is the process of extracting(Output) data from an instance of output data into some user-specified format .
- ❑ **load** and **save** are used to **import** and **export** data.

3

1ST

IMPORTING AND EXPORTING DATA

Other import/export functions

- ❑ with differing degrees of flexibility and ease of use, include **csvread**, **csvwrite**, **dlmread**, **dlmwrite**, **fgets**, **fprintf** (which has an optional argument to specify a file), **fscanf**, **textread**, **xlsread** , **xlswrite** You know where to look for the details!
- ❑ ‘-mat’ Keyword that indicates that the specified file is a MAT-file.
- ❑ ‘-ascii’ Keyword that indicates that the specified file is an ASCII file.

4

1ST

IMPORTING AND EXPORTING DATA**1. The save command :-**

If you want to store the data into an ASCII dat-file (in the current directory), make the filename the same as the name of the data and type ‘**/ascii**’ at the end of the **save** statement.

Syntax**save (filename)**

Save all workspace variables to (....mat)

save(filename, variables)

stores only the specified variables

save (filename, ... ,format)

saves in the specified format'-mat' or '-ascii'

5

1ST

Ex:- Save data to an ASCII file ,and view the contents of the file with the type function.

```
>> p = rand(1, 10);
>> q = ones(10);
>> save('pqfile.txt','p','q','-ascii')
>> save('pqfile.mat','p','q','-mat')
or
>> save pqfile.txt p q -ascii
>> save pqfile.mat p q -mat
```

- The extension -.mat is the default—you can specify a different extension.

6

1ST

IMPORTING AND EXPORTING DATA

2. The load command :-

The **load** command is the reverse of save. It is used to Importing text (ASCII) data or load data from MAT-file into workspace .

Syntax

S=load (filename)

S=load (filename, variables)

S=load (filename, format ,variables) load in the specified format'-mat' or '-ascii'

load (filename, ____) loads without combining MAT-file variables into a structure array .

7

1ST

IMPORTING AND EXPORTING DATA

```
>> p = rand(1, 10);
>> q = ones(10);
>> save pqfile p q
>> clear all
>> p
Undefined function or variable 'p'.
>> load pqfile p q
>> p
>> q
```

8

1ST

IMPORTING AND EXPORTING DATA**EXAMPLE 1: THE PRECIPITATION**

This example show you how to load a simple data set and plot it.

The PDXprecip.dat file contains two columns of numbers. The first is the number of the month, and the second is the mean precipitation recorded at the Portland International Airport between 1961 and 1990. Here are the MATLAB commands to create a symbol plot with the data from PDXprecip.dat.

9

1ST

IMPORTING AND EXPORTING DATA**EXAMPLE 1: THE PRECIPITATION****PDXprecip.dat**

1	5.35
2	3.68
3	3.54
4	2.39
5	2.06
6	1.48
7	0.63
8	1.09
9	1.75
10	2.66
11	5.34
12	6.13

- ✓ Documents → MATLAB → R.Click :New → Text Document
write the table above and save it as PDXprecip.dat


10

1ST

script-file precipPlot.m :

```
% Filename: precipPlot.m
% Load data from PDXprecip.dat and plot it with symbols
% read data into PDXprecip matrix
clc,clear all
load PDXprecip.dat;
% copy first column of PDXprecip into month and second
%column into precip
month = PDXprecip(:,1);
precip = PDXprecip(:,2);
plot(month , precip,'o');    % plot precip vs. month with circles
xlabel('month of the year'); % add axis labels and plot title
ylabel('mean precipitation (inches)');
title('Mean monthly precipitation at Portland International Airport');
```

1ST

IMPORTING AND EXPORTING DATA

12

1ST

IMPORTING AND EXPORTING DATA

3. The xlsread command :- Read Microsoft Excel spreadsheet file (.xlsx) ,retrieving or Importing data .

Syntax

```
num = xlsread(filename)
num = xlsread(filename , sheet)
num = xlsread(filename , xlRange)
num = xlsread(filename , sheet , xlRange)
num = xlsread(filename , sheet, xlRange , 'basic')
[num , txt , raw] = xlsread(___)
____ = xlsread(filename,-1)
```

13

1ST

IMPORTING AND EXPORTING DATA

- num= xlsread(filename)**
 - Read and returns numeric data in **double** array **num** from the first sheet in the Microsoft Excel spreadsheet file named **filename**.
- num= xlsread(filename,-1)**
 - Opens the file **filename** in an Excel window, enabling you to interactively select the worksheet to be read and the range of data on that worksheet to import.
- num= xlsread(filename, sheet)**
 - Reads the specified worksheet, where **sheet** is either a positive, double scalar value or a quoted string containing the sheet name.

14

1ST

IMPORTING AND EXPORTING DATA**num= xlsread(filename, xlRange)**

- Reads data from a specific rectangular region of the default worksheet (**Sheet1**). Specify **range** using the syntax '**C1:C2**', where **C1** and **C2** are two opposing corners that define the region to be read.

num=xlsread(filename , sheet, xlRange)

- Reads data from a specific rectangular region (**range**) of the worksheet specified by **sheet**.

num= xlsread(filename, sheet , xlRange, 'basic')

- Imports data from the spreadsheet in basic import mode. This is the mode used on UNIX platforms as well as on Windows when Excel is not available as a **COM server**.

15

1ST

IMPORTING AND EXPORTING DATA**[num,txt,raw]= xlsread(filename, ...)**

- Returns numeric and text data in **num** and **txt**, and unprocessed cell content in cell array **raw**, which contains both numeric and text data.

Example :- Read Data from First Worksheet into Numeric Array .

- Create an Excel file named **myExample.xlsx**

```
>> values = {1, 2, 3 ; 4, 5, 'x' ; 7, 8, 9};  
% to define a subset of the array. Enclose indices in curly  
brackets, { }, to refer to the text, numbers, or other data  
within individual cells.  
>> headers = {'First','Second','Third'};  
>> xlswrite('myExample.xlsx',[headers; values]);
```

16

1ST

IMPORTING AND EXPORTING DATA

- Read data from the first worksheet

```
>> filename = 'myExample.xlsx';
>> A = xlsread(filename)
or
>> A = xlsread('myExample.xlsx')
A =
    1   2   3
    4   5   NaN
    7   8   9
>> [num text raw]=xlsread('myExample.xlsx')
```

- ❖ xlsread returns the numeric data in array A .

17

1ST

```
>> [num text raw]=xlsread('myExample.xlsx')
num =
    1   2   3
    4   5   NaN
    7   8   9
text =
    'First'  'Second'  'Third'
    "        "        "
    "        "        'x'
raw =
    'First'  'Second'  'Third'
    [ 1]  [ 2]  [ 3]
    [ 4]  [ 5]  'x'
    [ 7]  [ 8]  [ 9]
```

18

1ST

IMPORTING AND EXPORTING DATA

EXAMPLE 2: READ A SPECIFIC RANGE OF DATA FROM THE EXCEL FILE IN THE PREVIOUS EXAMPLE.

```
>> filename = 'myExample.xlsx';
>> sheet = 1;
>> xlRange = 'B2:C3';
>> subsetA = xlsread(filename, sheet, xlRange)
subsetA =
    2      3
    5      NaN
```

19

1ST

IMPORTING AND EXPORTING DATA

EXAMPLE 3: Import data of the outdoor temperature, Sunlight radiation, pressure and the relative humidity from nivada.xlsx
Do four plots of outdoor temperature, sunlight radiation, pressure, and relative humidity versus time (hours) for Nivada dataset 2007 for four months (Jan. to Apr.)

	A	B	C	D	E	F	G	H	I	J	K	L
1	Year	Day of Year	Month	Day	Hour	Solar Altitude	Solar Energy(W/m ²)	Air Temp(C°)	Wind Speed(m/s)	Wind Dir	Pressure(h pa)	RH %
2	2007	1	1	1	0	-73	0	-6.9	0.9	193	907	72
3	2007	1	1	1	1	-64	0	-7	1	147	907	73
4	2007	1	1	1	2	-52	0	-8.4	0.9	188	908	77
5	2007	1	1	1	3	-40	0	-7.8	1	194	908	78
6	2007	1	1	1	4	-29	0	-9.4	0.9	174	908	81
7	2007	1	1	1	5	-17	0	-8.9	1.1	193	909	82
8	2007	1	1	1	6	-6	1	-7.5	1.3	180	909	78
9	2007	1	1	1	7	5	58	-6.5	1	162	910	78
10	2007	1	1	1	8	14	228	2.5	1.8	336	910	51
11	2007	1	1	1	9	22	373	7.7	2.3	55	910	38
12	2007	1	1	1	10	27	476	10.4	4.3	40	910	32
13	2007	1	1	1	11	30	524	11.8	6.2	30	909	29
14	2007	1	1	1	12	29	511	12.5	6.2	49	908	28
15	2007	1	1	1	13	25	439	12.9	5.8	10	908	27
16	2007	1	1	1	14	19	317	12.9	5.5	342	908	27
17	2007	1	1	1	15	10	163	12	5	288	908	28
18	2007	1	1	1	16	0	21	9.3	3.7	34	908	33
19	2007	1	1	1	17	-10	0	5.9	1.6	110	909	39
20	2007	1	1	1	18	-22	0	6	2.8	30	910	41
21	2007	1	1	1	19	-34	0	3.8	1.1	166	911	45
22	2007	1	1	1	20	-46	0	4.3	3.1	21	911	46
23	2007	1	1	1	21	-57	0	4.8	2.5	24	912	44
24	2007	1	1	1	22	-68	0	5.1	3.3	30	912	43
25	2007	1	1	1	23	-75	0	3.7	3.2	33	912	48

20

1ST

script-file [myNivada.m](#) :

```
% Filename: myNivada.m
% by Thaer O. Roomi (2014)
% This program plots the values of temperature, sunlight radiation,
% Average pressure, and Relative Humidity for hourly averages
% versus the time (hours) for four months (1,2,3 and 4) 2007.
clear all
[num txt]=xlsread('nivada.xlsx');
year=num(:,1); day_of_year=num(:,2); hour=num(:,5);
DateNumber = datenum(year,month,day,hour,0,0);
temperature=num(:,8);
sunlight=num(:,7);
pressure=num(:,11);
relhum=num(:,12);
```

1ST

```
% divided figure into 4-plots
subplot(2,2,1)
plot(DateNumber, temperature)
xlabel('Time [hours]')
ylabel('Temperature [degrees C]')
title('Outdoor temperature in Nivada 2007')
%datetick('x','mmm','keepticks')
%datetick('x','mmm-dd (ddd)','keepticks')
%datetick('x','HHPM','keepticks')
datetick('x','yyyy-mmm','keepticks')
```

22

1ST


```
subplot(2,2,2)
plot(DateNumber,sunlight)
xlabel('Time [hours]')
ylabel('Sunlight radiation [W/m^2]')
title('Sunlight radiation in Nivada 2007')
datetick('x','yyyy-mmm','keepticks')
subplot(2,2,3)
plot(DateNumber,pressure)
xlabel('Time [hours]')
ylabel('Pressure [hPa]')
title('Average station pressure in Nivada 2007')
datetick('x','yyyy-mmm','keepticks')
```

23

1ST

```
grid on
subplot(2,2,4)
plot(DateNumber,relhum)
xlabel('Time [hours]')
ylabel('Relative Humidity [%]')
title('Relative Humidity in Nivada')
datetick('x','yyyy-mmm','keepticks')
```

24



1ST

IMPORTING AND EXPORTING DATA**`xlswrite(filename ,A)`**

- Writes array **A** to the first worksheet in Excel file, **filename**, starting at cell **A1**.

`xlswrite(filename ,A, sheet)`

- Writes to the specified worksheet.

`xlswrite(filename ,A, xlRange)`

- Writes to the rectangular region specified by **xlRange** in the first worksheet of the file.

`xlswrite(filename ,A, sheet, xlRange)`

- Writes to the specified **sheet** and range, **xlRange**.

27

1ST

IMPORTING AND EXPORTING DATA

Example :- Write Data to a Spreadsheet First. Write a 7-element vector to an Excel file, testdata.xlsx.

```
>> filename = 'testdata.xlsx';
>> A = [12.7, 5.02, -98, 63.9, 0, -.2, 56];
>> xlswrite(filename , A)
```

Example :- Write Data to a Specific Sheet and Range in a Spreadsheet. Write mixed text and numeric data to an Excel file, testdata.xlsx, Starting at cell E1 of Sheet2.

```
>> filename = 'testdata.xlsx';
>> A = {'Time', 'Temperature'; 12.98; 13.99; 14.97};
>> sheet = 2;
>> xlRange = 'E1';
>> xlswrite(filename, A, sheet , xlRange)
```

1ST

IMPORTING AND EXPORTING DATA

Homework

Write a MATLAB program to read the numerical and analytical solutions in table (1) from excel sheet file to calculate the mean of the numerical values, “Quarter,Hourly,Simidiurnal,Diurnal”

Note: use an Excel spreadsheet to reading and writing values. Then draw each of numerical values versus the time steps.

29

1ST

IMPORTING AND EXPORTING DATA

	A	B	C	D	E
1		LONGWAVE SOLAR RADIATION			
2		Time (hour)	Wm ⁻²		
3	1	10/21/2014 12:00:0	366.946		
4	1	10/21/2014 12:15:0	375.059		
5	1	10/21/2014 12:30:0	377.508		
6	1	10/21/2014 12:45:0	379.093		
7	1	10/21/2014 1:00:00	371.259		
8	1	10/21/2014 1:15:00	371.807		
9	1	10/21/2014 1:30:00	360.323		
10	1	10/21/2014 1:45:00	334.417		
11	1	10/21/2014 2:00:00	335.704		
12	1	10/21/2014 2:15:00	352.121		
13	1	10/21/2014 2:30:00	340.177		
14	1	10/21/2014 2:45:00	343.073		
15	1	10/21/2014 3:00:00	347.619		
16	1	10/21/2014 3:15:00	342.998		
17	1	10/21/2014 3:30:00	341.575		
18	1	10/21/2014 3:45:00	337.019		

30

1ST

IMPORTING AND EXPORTING DATA

```

clear all , clc
[A date]=xlsread('long_w.xlsx');
C=A(:,3);           % Read data
h=0;                 % new index for the new values
n=numel(C);          % number of elements in the excel
sheet
for i=1:4:n-3        % read i =1,5,9,...n-3
    h=h+1; % to add 1 to index h=1,2,3,4,....
    C_mean_4(h)=mean(C([i:i+3])); % find mean value for
each 4 elements of the array
end
if mod(n,4)~=0;
    C_mean_4(h+1)= mean(C(n-mod(n,4):end));
end

```

1

1ST

IMPORTING AND EXPORTING DATA

```

h=numel(C_mean_4)
C_M_4=C_mean_4';
k=0;
for i=1:12:h-11
    k=k+1;
    C_mean_12(k)=mean(C_M_4([i:i+11]));
end
if mod(h,12)~=0;
    C_mean_12(k+1)= mean(C_M_4(n-mod(n,12):end));
end
k=numel(C_mean_12);
C_M_12=C_mean_12';

```

2

1ST

IMPORTING AND EXPORTING DATA

```
kk=0;
for i=1:24:h-23
    kk=kk+1;
    C_mean_24(kk)=mean(C_M_4([i:i+23]));
end
if mod(h,24)~=0;
    C_mean_24(kk+1)= mean(C_M_4(n-mod(n,24):end));
end
kk=numel(C_mean_24);
C_M_24=C_mean_24';
```

1ST

IMPORTING AND EXPORTING DATA

```
filename='long_w.xlsx';
sheet = 2;
DD={'Time in
Year','Time','Quarter','Time','HOURLY','Time','SIMIDIURNAL','Ti
me','DIURNAL'};
date1=date([3:end],2);
t1=date1(1:4:end);
t2=date1(1:4*12:end);
t3=date1(1:4*24:end);sheet = 1;
```

1ST

IMPORTING AND EXPORTING DATA

```
xlswrite(filename,DD,sheet,'A1')  
xlswrite(filename,A(:,1),sheet,'A2')  
xlswrite(filename,date1,sheet,'B2')  
xlswrite(filename,C,sheet,'C2')  
xlswrite(filename,t1,sheet,'D2')  
xlswrite(filename,C_M_4,sheet,'E2')  
xlswrite(filename,t2,sheet,'F2')  
xlswrite(filename,C_M_12,sheet,'G2')  
xlswrite(filename,t3,sheet,'H2')  
xlswrite(filename,C_M_24,sheet,'I2')
```

1ST

IMPORTING AND EXPORTING DATA

```
d=datenum(date1);  
% datenum :Convert date and time to serial date number  
figure(1)  
hold on  
plot(d,C,:B')  
plot(d(1:4:end),C_M_4,:Y')  
plot(d(1:12*4:end),C_M_12,:G')  
plot(d(1:24*4:end),C_M_24,R')  
datetick('x','mmm','keepticks')  
xlabel('Time(hr)')  
ylabel('LongWave Solar Radiation (W/m^2)')  
title('Long Wave Solar Radiation')  
legend('QURTER','HOURLY','SIMIDIURNAL','DIURNAL')
```

1ST

IMPORTING AND EXPORTING DATA

Homework2

Write a MATLAB program to read data for Aerosol Optical Depth from Excel spreadsheet file AOD.xlsx to calculate the mean of monthly, seasonal and yearly .

37

1ST

IMPORTING AND EXPORTING DATA

	A	B	C	D	E
1	time	AOD			
2	2/24/2000	-9999			
3	2/25/2000	-9999			
4	2/26/2000	0.319			
5	2/27/2000	-9999			
6	2/28/2000	0.154			
7	2/29/2000	-9999			
8	3/1/2000	-9999			
9	3/2/2000	0.672			
10	3/3/2000	0.13			
11	3/4/2000	0.648			
12	3/5/2000	-9999			
13	3/6/2000	0.414			
14	3/7/2000	0.465			

38

1ST

IMPORTING AND EXPORTING DATA

```
% This is a program to calculate mean of monthly, seasonal  

and yearly data.  

clear all,clc  

[num txt]=xlsread('AOD.xlsx');  

date=txt(2:end,1);  

formatIn = 'mm/dd/yyyy';  

t=datenum(date,formatIn);  

c1=find(num==9999);  

t(c1)=[];num(c1)=[];  

y=year(t);m=month(t);d=day(t);  

AOD=num;  

%%%%% MEAN OF MONTHLY DATA %%%%%%  

h=0; % new index for the new values
```

1ST

IMPORTING AND EXPORTING DATA

```
for yy=2000:2016 % for yy=y(1):y(end)  

h=h+1;  

for mo=1:12  

in=find(y==yy);  

in1=find(m(in)==mo);  

monthly(h,mo)=nanmean(AOD(in1));  

end  

end  

filename='AOD.xlsx'; sheet=2;  

dd={'Jan','Feb','Mar','Apr','May','Jun','Jul','Aug','Sep','Oct','Nov','Dec'};  

xlswrite(filename,dd,sheet,'b1')  

xlswrite(filename,{'YEAR'},sheet,'A1')  

xlswrite(filename,[2000:2016],sheet,'a2')  

xlswrite(filename,monthly,sheet,'B2')
```

1ST

IMPORTING AND EXPORTING DATA

```
%%%%% MEAN OF SEASONAL DATA %%%%%%
winter=nanmean(monthly(:,[12,1,2])');
winter=winter';
spring=nanmean(monthly(:,[3,4,5])');
spring=spring';
summer=nanmean(monthly(:,[6,7,8])');
summer=summer';
autumn=nanmean(monthly(:,[9,10,11])');
autumn=autumn';
```

1ST

IMPORTING AND EXPORTING DATA

```
sheet=3;
ddd={'YEAR','Winter','Spring','Summer','Autumn'};
aa=[winter,spring,summer,autumn];
xlswrite(filename,ddd,sheet,'A1')
xlswrite(filename,[2000:2016],sheet,'a2')
xlswrite(filename,aa,sheet,'b2')
%%%%% MEAN OF YEARLY DATA %%%%%%
h=0;
for yy=2000:2016
    h=h+1;
    in=find(y==yy);
    yearly_mean(h)=nanmean(AOD(in));
end
```

1ST

IMPORTING AND EXPORTING DATA

```
sheet=4;  
xlswrite(filename,{'YEAR'},sheet,'A1')  
xlswrite(filename,[2000:2016],sheet,'a2')  
xlswrite(filename,{'AOD'},sheet,'B1')  
xlswrite(filename,yearly_mean,sheet,'B2')  
%%%%%%%%%%%%%
```