The Experiments of Weather Instruments & Observations lab.

(First Semester) ASD / 2nd Stage 2022 – 2023

Lecturers: L. Ruaa mazin , L. Hasan mahmood, A.L. Yasamin qusay

Preparing by: L. Ruaa M. Ibraheem, L. Nagham T. Ibraheem

Analysis and drawing of observation codes for

the upper atmosphere

Devices used for upper atmosphere observations:

- 1. Radiosonde
- 2. Pílot ballon
- 3. Radiowind
- 4. Satellites

Upper observations codes:

It observations the upper atmospheres for synoptic analyzes and weather forecasts in terms of atmospheric pressure, temperature, relative humidity, and wind speed and direction.

$M{\rm i}M{\rm i}M{\rm j}M{\rm j}$

The type of station and replace it with one of the following formulas:

If the report is from a fixed earth station (TTAA)

If the report was taken from a marine station (UUAA)

If the report was taken from a small balloon or balloon (XXAA)

If the report is from a portable station (IIAA)

YYGGI_d

Date and time codeThe date takes values between (01-31) or (51-81)YYTime and takes values between (00-23)GGEvidence of the last standard pressure level reached by the deviceId

	Γ	Γ	Γ	Γ	ſ	Γ	1	I	I	T	
code	1	2	3	4	5	6	7	8	9	0	/
Standard pressure level (hpa)	100	200	300	400	500	-	700	800	900	1000	There is no wind information in the report


IIiii

II Zone number / iii Station number

$99 P_0 P_0 P_0$ $T_0 T_0 T_{a0} D_0 D_0$ $d_0 d_0 d_0 f_0 f_0$

The code at the station's surface where:	
Atmospheric pressure	$P_oP_oP_o$
Temperature and tenths	$T_o T_o T_{ao}$
The difference between temperature and dew point	$D_o D_o$
Wind direction	$d_{\rm o}d_{\rm o}d_{\rm o}$
Wind speed	$f_o f_o$

• *The location of the weather elements on the station shall be as follows:*



- **1.** *The real value of the pressure level rise (hhh)*: *is calculated in a different way for each level, as will be mentioned in detail later, and it is measured in units (gpm).*
- **2.** The value of the dew point (T_dT_d) : is found according to the following equation for all standard levels

$T_dT_d = TTT_a - |DD|$

The temperature is **positive** if its tenths (T_a) are **even numbers**.

The temperature is **negative** if its tenths (T_a) are **odd numbers**.

DD is absolute and unsigned:

a - If its value is within (00-50), it is written in tenths.

22547 means its real value is 4.7

b - If its value is within (56-99), then we subtract 50 from it.

For example, 29458 means its real value is 8 as well as 15773 means 23.

c- The value of DD is plotted on the station as it is and applied in the above equation to get the value of $T_d T_d.$

3. Wind direction and speed:

a-Write the tens digit for the direction of the wind at the end of the arrow for accuracy.

b- *The wind speed remains the same when the date is added to 50, and the speed doubles when the date is normal, for example:*

28022 for the date 23121: the speed is 22 m/s and draws 44 knots

20050 for the date 80121: the speed remains the same, i.e. 50 knots

C - *If the wind speed is more than 100 kt. The hundreds digit is added to the ones in the direction, for example:*

28655: 285 direction / 155 speed

29700: 295 direction / 200 speed